



ITEM ID

7.80643

NAME/DESCRIPTION

Layered Raindrop Chandelier

DIMENSIONS / WEIGHT

Overall 29"L x 8.5"W x 99"H (27.12 lbs)

COUNTRY OF ORIGIN

China



URL

<https://www.globalviews.com/grouped-layered-raindrop-chandelier-14617>

ROMANCE

Suspended loops of soft glowing dimmable light offer a dramatic and functional accent to any environment. The LED light source located in each suspended light head interacts with air entrapped bubbles in the shaped acrylic rod to create a dramatic focal po

CARE & USE

Dust with dry cloth

MORE INFORMATION

Bulb/Candle Information: 22 PCS Integrate LED/ Cree XT-E

Cord/Chain Information: 6' Black fabric cord, cord is adjustable

Additional Information: Color Rendering: 90 CRI

Cord/Chain Information: Cord Max Length: 77"; Cord Minimum Length: 24" from the canopy to bottom of light

Additional Information: Dimmable, LED is replaceable by professional and LED Life expectancy is 3-5 years under normal use.

Additional Information: Driver Input Voltage: 120V Output Voltage: 21-42V Input Power: Max 18W Output Current: Max 350mA

Additional Information: Efficacy: lumen/Watt (Whole light) 50Lm/W; Efficacy: lumen/Watt (Only LED) 90Lm/W

Additional Information: It appears that the Acrylic should be free from yellowing for at a minimum 3 years, likely longer if the fixture is out of direct sunlight and fluctuating temperatures. The LEDs have a life expectancy of 18,000 hours which equates to 750 days if left burn

Additional Information: Kelvin rating: 2700K; Total Wattage: 26 W Max

Metal Finish: Satin Brass

Additional Information: This integrated LED lighting product has a five-year manufacturing warranty for defects.

Additional Information: UL Listed